

PCT


WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : A61M 16/00, A61B 5/0488		A1	(11) International Publication Number: WO 99/62580
			(43) International Publication Date: 9 December 1999 (09.12.99)
(21) International Application Number: PCT/CA99/00529		(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, L, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).	
(22) International Filing Date: 4 June 1999 (04.06.99)		<p>Published</p> <p><i>With international search report.</i></p> <p><i>Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i></p>	
(30) Priority Data: 2,239,673 4 June 1998 (04.06.98) CA			
(71) Applicant (for all designated States except US): UNIVERSITE DE MONTREAL [CA/CA]; 2900, boulevard Edouard-Montpetit, Montréal, Québec H3C 3J7 (CA).			
(72) Inventors; and (75) Inventors/Applicants (for US only): SINDERBY, Christer [CA/CA]; 12750 - 27th Avenue, Montreal, Quebec H1E 1Z9 (CA). BECK, Jennifer [CA/CA]; 12750 - 27th Avenue, Montreal, Quebec H1E 1Z9 (CA).			
(74) Agents: DUBUC, Jean, H. et al.; Goudreau Gage Dubuc & Martineau Walker, The Stock Exchange Tower, Suite 3400, 800, place Victoria, Montréal, Québec H4Z 1E9 (CA).			

(54) Title: PROPORTIONAL PRESSURE ASSIST VENTILATION CONTROLLED BY A DIAPHRAGM ELECTROMYOGRAPHIC SIGNAL



(57) Abstract

A closed loop system uses (a) the intensity of the diaphragm electromyogram (EMG) for a given inspiratory volume; (b) the inspiratory volume for a given EMG intensity; or (c) a combination of (a) and (b); in view of controlling the level of gas flow, gas volume or gas pressure delivered by a mechanical (lung) ventilator. The closed loop ventilator system enables for automatic or manual adjustment of the level of inspiratory support in proportion to changes in the neuro-ventilatory efficiency such that the neural drive remains stable at a desired target level. An alarm can also be used to detect changes in neuroventilatory efficiency in view of performing manual adjustments.